




OP4018B1

718.864 MHz Optical Timing Clock



SMC-8A

- Complies with Directive 2002/95/EC (RoHS)
- Fundamental-Mode Oscillation at 718.864 MHz
- Quartz SAW Stabilized and Filtered "Diff Sine" Technology
- Voltage Tunable for Phase Lock Loop Operations
- Optical Timing Reference for Forward Error Correction Applications



The output of this device is generated and filtered by narrowband quartz SAW elements at 718.864 MHz. The configuration of this clock is intended to provide a pure signal for optical timing applications in noisy signal environments. The Q/Qbar differential output swing of ± 1 volt about 0 vdc has symmetry better than $\pm 1\%$ into loads from 40 ohms to 70 ohms; determined by customer application. The long term frequency accuracy is set by an external reference source allowing this device to complete a Phase Lock Loop design without the usual noise and jitter problems associated with PLL's.

Absolute Maximum Ratings

Rating	Value	Units
DC Supply Voltage	0 to 5.5	VDC
Tune Voltage	0 to 6	VDC
Case Temperature	-55 to 100	°C

Electrical Characteristics


Characteristic	Sym	Notes	Minimum	Typical	Maximum	Units	
Operating Frequency	Absolute Frequency	f_0	1, 9		718.863785		MHz
		Tune Range	2	± 50			ppm
		Tune Voltage	1	1.8	2.4	3	VDC
		Tuning Linearity	1, 8	± 5	3	5	%
		Modulation Bandwidth			100		kHz
		Tune DC resistance			100		K Ω
		Deviation Slope			150	250	350
Q and Q Output	Voltage into 50 Ω (VSWR \leq 1.2)	V_O	1, 3	0.6		1.1	V _{P-P}
		Operating Load VSWR	1, 3			2:1	
		Symmetry	3, 4, 5	49		51	%
		Harmonic Spurious	3, 4, 6			-15	dBc
		Nonharmonic Spurious	3, 4, 6, 7			-65	dBc
Phase Noise	dBc/Hz@100Hz offset	1kHz offset		-70	-65	dBc/Hz	
		10k offset		-100	-95	dBc/Hz	
		100k offset		-125	-120	dBc/Hz	
		100k offset		-140	-135	dBc/Hz	
		Noise Floor		-150			dBc/Hz
Jitter	RMS Jitter (10kHz to 80MHz)		3, 4, 6, 7			0.5	PS _{P-P}
		200 mV _{P-P} from 1MHz to $\frac{1}{2} f_0$ on V _{CC}	3			-50	dBc
Output DC Resistance (between Q & Q)		1, 3	50			K Ω	
DC Power Supply	Operating Voltage	V _{CC}	1, 3	3.135	3.300	3.465	VDC
		Operating Current	I _{CC}	1, 3			70
Operating Ambient Temperature		T _C	1, 3	0°C		+85°C	°C
Lid Symbolization (YY=Year, WW=Week)	RFM OP4018B YYWW						




CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.
COCOM CAUTION: Approval by the U.S. Department of Commerce is required prior to export of this device.

Notes:

1. Unless otherwise noted, all specifications include any combination of load VSWR, V_{CC}, and T_C. In addition, Q and \bar{Q} are terminated into 50 Ω loads to ground. (See: Typical Test Circuit.)
2. Customer useful tune range in excess of what part requires over temp, aging, pushing, pulling & accuracy.
3. The design, manufacturing process, and specifications of this device are subject to change without notice.
4. Only under the nominal conditions of 50 Ω load impedance with VSWR \leq 1.2 and nominal power supply voltage.
5. Symmetry is defined as the pulse width (in percent of total period) measured at the 50% points of Q or \bar{Q} . (See: Timing Definitions.)
6. Jitter and other spurious outputs induced by externally generated electrical noise on V_{CC} or mechanical vibration are not included in this specification, except where noted. External voltage regulation and careful PCB layout are recommended for optimum performance.
7. Applies to period jitter of Q and \bar{Q} . Measurements are made with the Tektronix CSA803 signal analyzer with at least 1000 samples.
8. Linearity is a function of the percentage variation from a permitted linear deviation versus the amount of frequency tune range. See *Linearity Definition*.
9. One or more of the following United States patents apply: 4,616,197; 4,670,681; 4,760,352.




BLOCK DIAGRAM




Typical Printed Circuit Board Land Pattern

A typical land pattern for a circuit board is shown below. Grounding of the metallic center pad is optional.



Electrical Connections

Terminal Number	Connection
1	Tune
2	*Enable
3	Ground
4	Ground
5	Q Output
6	Q̄ Output
7	V _{CC}
8	Ground
LID	Ground



Dimensions

Dimension	mm		Inches	
	MIN	MAX	MIN	MAX
A	13.46	13.97	0.530	0.550
B	9.14	9.66	0.360	0.380
C	1.93 Nominal		0.076 Nominal	
D	1.93 Nominal		0.076 Nominal	
E	2.54 Nominal		0.100 Nominal	
F	1.27 Nominal		0.050 Nominal	

*Enable Sense: Pin 2 Ground-Clock Off

