



RO2188

**390.0 MHz
SAW
Resonator**

- **Ideal for 390.0 MHz Transmitters**
- **Very Low Series Resistance**
- **Quartz Stability**
- **Rugged, Hermetic, TO39-3 Package**
- **Complies with Directive 2002/95/EC (RoHS)**



The RO2188 is a true one-port, surface-acoustic-wave (SAW) resonator in TO39-3 case. It provides reliable, fundamental-mode, quartz frequency stabilization of fixed-frequency transmitters operating at 390.0 MHz.

Absolute Maximum Ratings

Rating	Value	Units
CW RF Power Dissipation	+5	dBm
DC Voltage Between Any Two Pins (Observe ESD Precautions)	±30	VDC
Case Temperature	-40 to +85	°C



TO39-3 Case

Electrical Characteristics

Characteristic		Sym	Notes	Minimum	Typical	Maximum	Units
Center Frequency at +25 °C	Absolute Frequency	f_C	2, 3, 4, 5	389.900		390.100	MHz
	Tolerance from 304.0 MHz	Δf_C					
Insertion Loss		IL	2, 5, 6		0.9	2.0	dB
Quality Factor	Unloaded Q	Q_U	5, 6, 7		12,000		
	50 Ω Loaded Q	Q_L			1,200		
Temperature Stability	Turnover Temperature	T_O	6, 7, 8	27	42	57	°C
	Turnover Frequency	f_O		$f_C - 5$			kHz
	Frequency Temperature Coefficient	FTC		0.037			ppm/°C ²
Frequency Aging	Absolute Value during the First Year	fA	1		≤10		ppm/yr
DC Insulation Resistance between Any Two Terminals			5	1.0			MΩ
RF Equivalent RLC Model	Motional Resistance	R_M	5, 7, 9		11	26	Ω
	Motional Inductance	L_M			54.963		μH
	Motional Capacitance	C_M			3.0299		fF
	Pin 1 to Pin 2 Static Capacitance	C_O		5, 6, 9	3.6	3.9	4.2
	Transducer Static Capacitance	C_P	5, 6, 7, 9		3.65		pF
Test Fixture Shunt Inductance		L_{TEST}	2, 7		43		nH
Lid Symbolization					E319		



CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.


Notes:

- Lifetime (10 year) frequency aging.
- The center frequency, f_C , is measured at the minimum insertion loss point, IL_{MIN} , with the resonator in the 50 Ω test system (VSWR ≤ 1.2:1). The shunt inductance, L_{TEST} , is tuned for parallel resonance with C_O at f_C .
- One or more of the following United States patents apply: 4,454,488 and 4,616,197.
- Typically, equipment utilizing this device requires emissions testing and government approval, which is the responsibility of the equipment manufacturer.
- Unless noted otherwise, case temperature $T_C = +25°C ± 2°C$.
- The design, manufacturing process, and specifications of this device are subject to change without notice.
- Derived mathematically from one or more of the following directly measured parameters: f_C , IL, 3 dB bandwidth, f_C versus T_C , and C_O .
- Turnover temperature, T_O , is the temperature of maximum (or turnover) frequency, f_O . The nominal frequency at any case temperature, T_C , may be calculated from: $f = f_O [1 - FTC (T_O - T_C)^2]$.
- This equivalent RLC model approximates resonator performance near the resonant frequency and is provided for reference only. The capacitance C_O is the static (nonmotional) capacitance between the two terminals measured at low frequency (10 MHz) with a capacitance meter. The measurement includes parasitic capacitance with a floating case. Case parasitic capacitance is approximately 0.25pF. Transducer parallel capacitance can be calculated as: $C_P = C_O - 0.25pF$.

Electrical Connections

This one-port, two-terminal SAW resonator is bidirectional. The terminals are interchangeable with the exception of circuit board layout.


Pin	Connection
1	Terminal 1
2	Terminal 2
3	Case Ground




Typical Test Circuit

The test circuit inductor, L_{TEST} , is tuned to resonate with the static capacitance, C_0 at F_C .

Electrical Test:




Power Test:




Typical Application Circuits

Typical Low-Power Transmitter Application:




Typical Local Oscillator Application:




Temperature Characteristics

The curve shown on the right accounts for resonator contribution only and does not include oscillator temperature characteristics.




Equivalent LC Model

The following equivalent LC model is valid near resonance:



Case Design



Dimensions	Millimeters		Inches	
	Min	Max	Min	Max
A		9.40		0.370
B		3.18		0.125
C	2.50	3.50	0.098	0.138
D	0.46 Nominal		0.018 Nominal	
E	5.08 Nominal		0.200 Nominal	
F	2.54 Nominal		0.100 Nominal	
G	2.54 Nominal		0.100 Nominal	
H		1.02		0.040
J	1.40		0.055	